

METALFORM

MASTERS OF METAL

**SA 15 Inward and Outward Opening Doors and
Windows | Brass OT67**

METALFORM

SA 15 Inward and Outward Opening Doors and Windows | Brass OT67

- Supply and installation of doors, windows, and facades, in fixed and openable sashes, for inward and outward opening doors and windows, built with tubular profiles Secco Sistemi SA 15, closed by mechanical coupling (UNI EN 10142/3/7 standards), obtained by cold-rolling profiling of Copper alloy OT67 (Cu67/Zn33) with thickness 15/10, in accordance with the EN1652:1999 standard.
- The folding unit must be kept open so that the stainless steel alignment brackets can be inserted, even in the case of continuous surface welding.
- The assembly of the frames is carried out by welding the internal surfaces (which can't be viewed) with the insertion of internal stainless steel reinforcement brackets and eventual brazing of the parts which are visible.
- The windows have external and internal coplanarity profiles and the following visible sections: fixed side node of 45 mm, openable side node of 81 mm, central node for the two sashes that is asymmetrical and measures 101mm / symmetrical 133mm, mandatory depth of 55mm.
- The doors have internal and external profile coplanarity and the following visible sections: fixed 45 mm side node, opening side node of 106 mm, central node for the two wings 151mm, mandatory depth of 55mm.
- Water, air, and wind sealing system for inward opening windows with triple mortise gasket (two sealing levels, one of which is open-joint), for outward opening windows and for doors with double mortise gasket (one level of closed joint gasket).
- Mobile sill for floors for doors. A sufficient number of Corten steel screw-on water drains are provided in the windows.

METALFORM

- The frames are complete with glass, (insert glass type) fixed with glazing beads (select one of the following options) | Squared | Gothic | Thin | in brass OT67, spaced from the external surfaces by means of EPDM or silicone gaskets, and from the internal surfaces by means of pressure-inserted EPDM gaskets.
- The windows are equipped with concealed to be screwed on, hot burnished stainless steel adjustable, three-winged, with a capacity of 70kg per panel (Ø14 mm).
- The doors are equipped with locks with an adequate number of locking points proportioned with the height of the sashes and adjustable screw-on hinges with a load capacity of up to 100 kg (Ø22 mm) in hot burnished stainless steel.
- Oxidized Surfaces burnished with a mechanical cleaning process with abrasive, immersion in burnishing liquid, washing, and protection with Vaseline oil or a wax of your choice.
- The handles complete the set and are available in different shapes, materials, and finishes, including Brass OT67.

METALFORM

MASTERS OF METAL

UNITED KINGDOM

METALFORM

NORWAYMETAL LTD

53 Chelsea Manor Street

London, SW3 5RZ

SALES@METALFORM.UK

+44 20 81298814

GERMANY

METALFORM GMBH

Carl-Zeiss-Ring 15A

85737 Ismaning

SALES@METALFORMGROUP.DE

+49 17663630406

NORWAY

METALFORM AS

Brochmannsveien 2

1950 Rømskog

SALG@METALFORM.NO

+47 401 62 446

METALFORMGROUP

SALES@METALFORMGROUP.COM